

CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

ACOUSTICAL PERFORMANCE TEST REPORT

SCOPE OF WORK

ASTM E90 SOUND TRANSMISSION LOSS TESTING ON A 3-5/8" SINGLE STEEL STUD WALL,
WALL SYSTEM

REPORT NUMBER

K6244.01-303-11-R1

TEST DATE

01/27/20

ISSUE DATE REVISION DATE

02/11/20 02/14/20

RETENTION DATE

02/11/24


PAGES

12

DOCUMENT CONTROL NUMBER

RT-R-AMER-Test-2758 (01/24/19)

© 2017 INTERTEK



TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

REPORT ISSUED TO**CALIFORNIA EXPANDED METAL COMPANY (CEMCO)**

13191 Crossroads Parkway

North Suite 325

City of Industry, California

SECTION 1**SCOPE**

Intertek Building & Construction (B&C) was contracted by California Expanded Metal Company (CEMCO) to conduct a sound transmission loss test. Results obtained are tested values and were secured by using the designated test methods. The complete test data is included herein. The client provided the test specimen. All measurements were conducted in the HT test chambers at Intertek B&C located in Lake Forest, California.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. Intertek B&C will service this report for the entire test record retention period. The test record retention period ends four years after the test date. Test records, such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation, will be retained for the entire test record retention period.

For INTERTEK B&C:

COMPLETED BY:	Josue H. Vides	REVIEWED BY:	Leeland S. Hoover
TITLE:	Technician I	TITLE:	Laboratory Manager
	Acoustical Testing		Acoustical Testing
SIGNATURE:		SIGNATURE:	
DATE:	02/14/20	DATE:	02/14/20

JHV: LSH

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 2**SUMMARY OF TEST RESULTS**

SERIES/MODEL	3-5/8" Single Steel Stud Wall 24" O.C
TYPE	Wall System
DATA FILE NO.	K6244.01A
STC	53
OITC	35

SECTION 3**TEST METHODS**

The specimens were evaluated in accordance with the following:

ASTM E90-09 (2016), Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements

ASTM E413-16, Classification for Rating Sound Insulation

ASTM E1332-16, Standard Classification for Rating Outdoor-Indoor Sound Attenuation

ASTM E2235-04 (2012), Standard Test Method for Determination of Decay Rates for Use in Sound Insulation Test Methods

SECTION 4**SPECIMEN INSTALLATION**

The specimen was constructed in a 168" wide by 120" high by 12" deep steel frame test opening. Dense neoprene foam (3/8" thick by 3" wide) was adhered to the steel frame perimeter. Top and bottom plates and end studs were placed over the foam and fastened to the steel frame by TEK screws (3" long) with isolation washers.

TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 5**EQUIPMENT**

The equipment listed below meets the requirements of the test methods stated in Section 3 of this report.

EQUIPMENT

INSTRUMENT	MANUFACTURER	MODEL	DESCRIPTION	ASSET #	CAL DATE
Data Acquisition Card*	National Instruments	PXIe-4464	Data Acquisition Card	INT00392	09/19
Data Acquisition Card*	National Instruments	PXIe-4464	Data Acquisition Card	INT00395	10/19
Data Acquisition Card*	National Instruments	PXIe-4464	Data Acquisition Card	INT00625	11/18
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00234	03/19
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00235	03/19
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00236	03/19
Source Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00237	03/19
Source Room Microphone	PCB piezotronics	378C20	Microphone and Preamplifier	INT00238	03/19
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00229	04/19
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00230	04/19
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT01542	04/19
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00232	04/19
Receive Room Microphone	PCB Piezotronics	378C20	Microphone and Preamplifier	INT00233	04/19
Receive Room Environmental Indicator	Comet	T7510	Receive Room	INT00299	05/19
Source Room Environmental Indicator	Comet	T7510	Source Room	INT00300	05/19
Microphone Calibrator	Norsonic	1251	Acoustical Calibrator	INT00289	09/19

*- Note: The calibration frequency for this equipment is every two years per the manufacturer's recommendation.

TEST CHAMBER

VOLUME	DESCRIPTION
231 m ³	Rotating vane and stationary diffusers Temperature and humidity controlled Isolation pads under the floor
196 m ³	Stationary diffusers only Temperature and humidity controlled

MAXIMUM SIZE	DESCRIPTION
4.27 m wide by 3.05 m high	Vibration break between source and receive rooms

N/A-Not Applicable

TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 6**LIST OF OFFICIAL OBSERVERS**

NAME	COMPANY
Josue H. Vides	Intertek B&C
Marco T. Santa Rosa	Intertek B&C

SECTION 7**TEST PROCEDURE**

The sensitivity of the microphones was checked before measurements were conducted.

The transmission loss values were obtained for a single direction of measurement.

Two background noise sound pressure level and five sound absorption measurements were conducted at each of five microphone positions.

Two sound pressure level measurements were made simultaneously in receive and source rooms at each of five microphone positions.

The air temperature and relative humidity conditions were monitored and recorded during all measurements.

Data for flanking limit tests, repeatability measurements, and reference specimen tests are available upon request.

Intertek B&C will store samples of test specimens for four years.

TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 8**ACOUSTICAL TEST CALCULATIONS**

Transmission loss (TL) at each 1/3 octave frequency is the average source room sound pressure level minus the average receive room sound pressure level, plus, 10 times the log of the specimen area divided by the sound absorption of the receive room with the sample in place.

STC Rating

To obtain the Sound Transmission Class (STC), read the TL of the contour curve at 500 Hz. The sum of the deficiencies below the contour curve must not exceed 32. The maximum deficiency at any one frequency must not exceed 8.

OITC Rating

The Outdoor-Indoor Transmission Class (OITC) is calculated by subtracting the logarithmic summation of the TL values from the logarithmic summation of the A-weighted transportation noise spectrum stated in ASTM E1332.

TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 9
SPECIMEN DESCRIPTION

GYPSUM BOARD	One-Layer 5/8" Type X				
STUDS	3-5/8" 18 Mil/20EQ Steel, 24" O.C.				
INSULATION	Unfaced R-13 Insulation				
GYPSUM BOARD	Two-Layers 5/8" Type X				

MATERIAL	ACTUAL DIMENSIONS (inches)	ACTUAL THICKNESS (inches)	MANUFACTURER AND SERIES	QUANTITY	AVERAGE WEIGHT
GYPSUM BOARD	48" by 120"	5/8"	Gypsum Type X	3.5 sheets	2.1 lbs/ft ²
	<i>Note: Screws spaced on 12" centers on the field and 8" centers on the perimeter. Perimeter and joints sealed with acoustical sealant and foil tape. Screw heads sealed with foil tape.</i>				
STUD	1-1/2" by 120"	3-5/8"	CEMCO ViperStud 362VXS144-18 Mil/20EQ, (0.0190")	11 pieces	0.42 lbs/linear ft
	<i>Note: Spaced on 24" centers. Screwed to top and bottom plates.</i>				
INSULATION	24" by 120"	3-1/2"	R-13 Unfaced Fiberglass Insulation	7 batts	0.20 lbs/ft ²
	<i>Note: N/A</i>				
GYPSUM BOARD	48" by 120"	5/8"	Gypsum Type X	3.5 sheets	2.1 lbs/ft ²
	<i>Note: Screws spaced on 12" centers on the field and 8" centers on the perimeter. Perimeter and joints sealed with acoustical sealant and foil tape. Screw heads sealed with foil tape.</i>				
GYPSUM BOARD	48" by 120"	5/8"	Gypsum Type X	3.5 sheets	2.1 lbs/ft ²
	<i>Note: Screws spaced on 12" centers on the field and 8" centers on the perimeter. Perimeter and joints sealed with acoustical sealant and foil tape. Screw heads sealed with foil tape.</i>				

TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

TOP PLATES	1-1/4" by 168	3-5/8"	CEMCO ViperTrack 362VXT144-18 Mil/20EQ (0.0185")	1.5 pieces	0.40 lbs/linear ft
	<i>Note: N/A</i>				
BOTTOM PLATES	1-1/4" by 168	3-5/8"	CEMCO ViperTrack 362VXT144-18 Mil/20EQ (0.0185")	1.5 pieces	0.40 lbs/linear ft
	<i>Note: N/A</i>				

Photographs are included in Section 11.

The client did not supply a report drawing of the test specimen.

TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 10
TEST RESULTS
**ASTM E90
AIRBORNE SOUND TRANSMISSION LOSS**

 ACCREDITED
Testing Laboratory

TEST DATE	01/27/20				
DATA FILE NO.	K6244.01A				
CLIENT	California Expanded Metal Company (CEMCO)				
DESCRIPTION	Series/Model: Single Steel Stud Wall 24" O.C. with 1 Layer 5/8" Gypsum Type X Receive, 2 Layers 5/8" Gypsum Type X Source				
SPECIMEN AREA	13.01 m ²	RECEIVE TEMP.	17.7 °C	SOURCE TEMP	17.8 °C
TECHNICIAN	Marco T Sant	RECEIVE HUMIDITY	56%	SOURCE HUMIDIT	56%

FREQ (Hz)	BACKGROUND SPL (dB)	ABSORPTION (m ²)	SOURCE SPL (dB)	RECEIVE SPL (dB)	SPECIMEN TL (dB)	95% CONFIDENCE LIMIT	NUMBER OF DEFICIENCIES
80	38.6	8.3	102	87	17	1.50	-
100	34.3	6.6	102	82	23	1.08	-
125	42.2	6.0	103	71	35	0.96	2
160	42.6	5.7	104	70	37	0.93	3
200	37.2	6.7	107	69	41	0.65	2
250	27.0	7.2	107	65	45	0.45	1
315	27.7	7.3	107	62	47	0.48	2
400	32.5	6.1	106	59	50	0.34	2
500	19.8	5.2	107	59	52	0.25	1
630	18.1	5.6	107	56	54	0.23	0
800	22.8	5.7	105	53	56	0.35	0
1000	12.8	5.8	107	52	59	0.38	0
1250	12.5	5.9	105	50	58	0.14	0
1600	9.5	6.5	103	48	58	0.13	0
2000	7.9	7.8	102	51	53	0.30	4
2500	7.0	8.8	101	53	50	0.20	7
3150	7.5	9.9	101	48	54	0.25	3
4000	7.5	12.1	97	39	59	0.27	0
5000	7.2	15.4	93	30	62	0.50	-
STC RATING		53	(Sound Transmission Class)				
DEFICIENCIES		27	(Sum of Deficiencies)				
OITC RATING		35	(Outdoor-Indoor Transmission Class)				

Notes:

- 1) Receive Room levels less than 5 dB above the Background levels are red.
- 2) Specimen TL levels listed in red indicate the lower limit of the transmission loss.
- 3) Specimen TL levels listed in green indicate that there has been a filler wall correction applied


TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

ASTM E90
AIRBORNE SOUND TRANSMISSION LOSS

TEST DATE	01/27/20		
DATA FILE NO.	K6244.01A		
CLIENT	California Expanded Metal Company (CEMCO)		
DESCRIPTION	Series/Model: Single Steel Stud Wall 24" O.C. with 1 Layer 5/8" Gypsum Type X Receive, 2 Layers 5/8" Gypsum Type X Source		
SPECIMEN AREA	13.01 m ²	RECEIVE TEMP.	17.7 °C
TECHNICIAN	Marco T Sant	RECEIVE HUMIDITY	56%
		SOURCE TEMP	17.8 °C
		SOURCE HUMIDIT	56%



TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 11
PHOTOGRAPHS

Photo No. 1
Source Room View of Test Specimen



Photo No. 2
Receive Room View of Test Specimen

TEST REPORT FOR CALIFORNIA EXPANDED METAL COMPANY (CEMCO)

Report No.: K6244.01-303-11-R1

Date: 02/11/20

SECTION 12**REVISION LOG**

REVISION #	DATE	PAGES	REVISION
0	02/11/20	N/A	Original Report Issue
1	02/13/20	7,8	Section 9; Updated Stud Size from 18 Ga. To 18 Mil/20EQ. Updated Top Plates & Bottom Plates to 18 Mil/20EQ.