

TYPICAL STEEL
FASTENERS BY DESIGN

FLUTED METAL DECK
WITH CONCRETE FILL

3/8" NOMINAL GAP
(3/4" JOINT PROTECTION)

MINERAL WOOL

5/8" TYPE "X" DRYWALL

CEMCO FAS J-TRACK

1" SHAFT LINER

CH STUD

NOTE: SINGLE LAYER OF 5/8" TYPE "X" DRYWALL FOR 1 HOUR FIRE RATING

HW-D-0525

SHAFT WALL, PERPENDICULAR TO FLUTED DECK

ASSEMBLY RATING: 2 HR



WWW.CEMCOSTEEL.COM
263 N. Covina Lane.
City of Industry, CA 91744
PHONE (800) 775-2362
ENG. DEPT.
FAX (626) 369-7243
WWW.CEMCOSTEEL.COM

DISCLAIMER:

CEMCO assumes no liability for failure resulting from the use of it's drawings, computations, or for failure resulting from the use of alternate materials, or improper application or installation. This drawing is supplied solely to assist in the selection and application of CEMCO products. This drawing is generic in nature and should not be used in design or construction without an independent evaluation by a qualified Architect or Engineer of Record. All warranties of any kind, express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose are disclaimed.

REVISION:

DRAWN BY: T. GARIBEKIAN
DATE: 11/09/19

APPROVED BY: F. SESMA
DATE: 11/09/19

SCALE: 3" = 1'-0"

JOB NO.: UL DETAILS

SHEET NO.:

SD115.1