



NOTE: SINGLE LAYER OF $\frac{5}{8}$ " TYPE "X" DRYWALL FOR 1 HOUR FIRE RATING

HW-D-0623	SHAFT WALL, @ FLUTED DECK BEAM PENETRATION	
ASSEMBLY RATING: 2 HR		
 <p>WWW.CEMCOSTEEL.COM 263 N. Covina Lane. City of Industry, CA 91744 PHONE (800) 775-2362 ENG. DEPT. FAX (626) 369-7243 WWW.CEMCOSTEEL.COM</p>	<p>DISCLAIMER:</p> <p>CEMCO assumes no liability for failure resulting from the use of its drawings, computations, or for failure resulting from the use of alternate materials, or improper application or installation. This drawing is supplied solely to assist in the selection and application of CEMCO products. This drawing is generic in nature and should not be used in design or construction without an independent evaluation by a qualified Architect or Engineer of Record. All warranties of any kind, express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose are disclaimed.</p>	<p>REVISION:</p> <p>DRAWN BY: T.GARIBEKIAN DATE: 11/09/19</p> <p>APPROVED BY: F. SESMA DATE: 11/09/19</p> <p>SCALE: 3" = 1'-0"</p> <p>JOB NO.: UL DETAILS</p> <p>SHEET NO.:</p> <p>SD118</p>