

CONCRETE SLAB OR FLUTED
METAL DECK WITH CONCRETE FILL

SPRAY
FIREPROOFING

STEEL BEAM

STRUCTURAL FIREPROOFING
(THICKNESS BY OTHERS)

DEFLECTION DRIFT
ANGLE DDA-1
(ONE SIDE ONLY)

1" JOINT PROTECTION

1/2" x 20 GA. Z-BAR OR
16 GA. CRC @ 16" O.C.

MINERAL WOOL

CEMCO SLOTTED
TRACK

5/8" TYPE "X" DRYWALL

1" SHAFT LINER

CH STUD

NOTE: SINGLE LAYER OF 5/8" TYPE "X" DRYWALL FOR 1 HOUR FIRE RATING

HW-D-0622

SHAFT WALL, OFFSET UNDER BEAM

ASSEMBLY RATING: 2 HR



WWW.CEMCOSTEEL.COM

263 N. Covina Lane.
City of Industry, CA 91744
PHONE (800) 775-2362
ENG. DEPT.
FAX (626) 369-7243
WWW.CEMCOSTEEL.COM

DISCLAIMER:

CEMCO assumes no liability for failure resulting from the use of its drawings, computations, or for failure resulting from the use of alternate materials, or improper application or installation. This drawing is supplied solely to assist in the selection and application of CEMCO products. This drawing is generic in nature and should not be used in design or construction without an independent evaluation by a qualified Architect or Engineer of Record. All warranties of any kind, express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose are disclaimed.

REVISION:

DRAWN BY: T.GARIBEKIAN
DATE: 12/12/2019

APPROVED BY: F. SESMA
DATE: 12/12/2019

SCALE: 3"=1'-0"

JOB NO.: UL DETAILS

SHEET NO.:

SD100