



NOTE: DOUBLE LAYERS OF  $\frac{5}{8}$ " DRYWALL FOR 2 HOUR FIRE RATING

HW-D-0624	STANDARD WALL, CONCRETE SLAB	
ASSEMBLY RATING: 1 HR	DISCLAIMER:	REVISION:
 <a href="http://WWW.CEMCOSTEEL.COM">WWW.CEMCOSTEEL.COM</a> 263 N. Covina Lane. City of Industry, CA 91744 PHONE (800) 775-2362 ENG. DEPT. FAX (626) 369-7243 <a href="http://WWW.CEMCOSTEEL.COM">WWW.CEMCOSTEEL.COM</a>	<p>CEMCO assumes no liability for failure resulting from the use of its drawings, computations, or for failure resulting from the use of alternate materials, or improper application or installation. This drawing is supplied solely to assist in the selection and application of CEMCO products. This drawing is generic in nature and should not be used in design or construction without an independent evaluation by a qualified Architect or Engineer of Record.</p> <p>All warranties of any kind, express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose are disclaimed.</p>	DRAWN BY: T. GARIBEKIAN DATE: 03/21/2016
		APPROVED BY: DON PILZ DATE: 03/21/2016 SCALE: 3"=1'-0"
		JOB NO.: UL DETAILS SHEET NO.:
		<b>SD144</b>